



CL/PLUS/EC

- E.C. TECHNOLOGY MOTOR WITH BUILT-IN ELECTRONICS
- INSPECTION HATCH FOR EASY MAINTENANCE
- 40MM THICK ACOUSTIC CASING
- EASY TO INSTALL IN ANY POSITION



IN-LINE EXTRACT FANS
FOR RECTANGULAR DUCTS

CL/PLUS/EC

The CL/PLUS/EC in-line fan line has been designed for installation in tight spaces and false ceilings.

The 40 mm thick acoustic casing, which reduces noise through the use of high-quality insulation materials designed for these applications, makes it the perfect fan for installation in applications that require low noise levels.

Saving energy is an important consideration when selecting this fan. The high performance E.C. Technology electric motor is a key element in reducing electrical consumption, in addition to being easy to regulate with any 0-10V signal.

Specially designed for easy installation in rectangular ducts, it is easy to maintain thanks to its inspection hatch and backward curved impeller blades, which minimise the build-up of dust and dirt.



CL/PLUS/EC



In-line extract fans for rectangular ducts with a 40 mm thick acoustic casing to reduce noise and E.C. Technology motor.



Fan:

- Galvanised sheet steel casing.
- 40mm thick acoustic casing.
- Impeller with backward curved blades.
- Linear airflow direction.
- Fitted with a folding inspection hatch for ease of maintenance.

- Single-phase 200-240V– 50/60Hz and three-phase 380-480V– 50/60Hz.
- Temperature of air through fan: -25°C to +60°C

Finish:

- Anti-corrosive finish on galvanised sheet steel.

Motor:

- High efficiency E.C. Technology motors with external rotor, regulated by 0-10V signal.

Order code

CL/PLUS/EC — 5030

CL/PLUS/EC: In-line extract fans for rectangular ducts with acoustic insulation and E.C. Technology motor.

Connection dimensions

Technical characteristics

Model	Speed (r/min)	Maximum admissible current (A)		Max. electric power (W)	Maximum flow rate (m³/h)	Sound pressure level at 50% of max. speed* dB(A)	Weight (kg)	According ErP
		230V	400V					
CL/PLUS/EC-3015	3570	1.01		127	591	31	12	2018
CL/PLUS/EC-4020	3265	1.35		176	958	36	17	2018
CL/PLUS/EC-5030	1920	1.35		175	1964	29	26	2018
CL/PLUS/EC-6030	2377	2		450	2080	35	35	2018
CL/PLUS/EC-6035	1550	2		460	3450	38	39	2018
CL/PLUS/EC-7040	2000		1.68	950	5650	39	51	2018
CL/PLUS/EC-8050	1250		2	1150	7315	36	66	2018

*Irradiated sound pressure level in dB(A) at a distance of 1.5 m and at maximum flow rate.



Erp. (Energy Related Products)

Information on Directive 2009/125/EC can be downloaded from the SODECA website or the QuickFan selector programme.

Accessories




Acoustic characteristics

Sound power spectrum Lw(A) in dB(A) per Hz frequency band.
Irradiated values at maximum speed and medium flow rate.

Model	63	125	250	500	1000	2000	4000	8000
CL/PLUS/EC-3015	33	43	42	47	45	46	45	41
CL/PLUS/EC-4020	50	50	43	50	44	42	45	45
CL/PLUS/EC-5030	30	44	33	32	44	25	24	19
CL/PLUS/EC-6030	31	46	48	51	50	51	46	40

Model	63	125	250	500	1000	2000	4000	8000
CL/PLUS/EC-6035	37	52	41	42	34	29	27	27
CL/PLUS/EC-7040	32	38	50	56	53	53	48	48
CL/PLUS/EC-8050	30	42	45	50	50	50	47	41

Dimensions mm




Model	A	B	C	D	E	ØF	G	H	J
CL/PLUS/EC-3015	385	235	335	150	300	Ø9	335	185	280
CL/PLUS/EC-4020	485	285	415	200	400	Ø9	435	235	330
CL/PLUS/EC-5030	495	385	495	300	500	Ø9	535	335	430
CL/PLUS/EC-6030	685	385	610	300	600	Ø9	635	335	430
CL/PLUS/EC-6035	685	435	610	350	600	Ø9	635	385	480
CL/PLUS/EC-7040	785	485	705	400	700	Ø9	735	435	540
CL/PLUS/EC-8050	885	585	825	500	800	Ø9	835	535	630

Characteristic curves

Flow rate in m³/h, m³/s and cfm.

Static pressure in mm H₂O, Pa and inwg.




Characteristic curves


Flow rate in m³/h, m³/s and cfm.

Static pressure in mm H₂O, Pa and inwg.

CL/PLUS/EC-4020





CL/PLUS/EC-5030



Characteristic curves

Flow rate in m³/h, m³/s and cfm.

Static pressure in mm H₂O, Pa and inwg.




Characteristic curves


Flow rate in m³/h, m³/s and cfm.

Static pressure in mm H₂O, Pa and inwg.

CL/PLUS/EC-7040



CL/PLUS/EC-8050





HEADQUARTERS

Sodeca, S.L.U.

Pol. Ind. La Barricona
Carrer del Metall, 2
E-17500 Ripoll
Girona, SPAIN
Tel. +34 93 852 91 11
Fax +34 93 852 90 42
General sales: comercial@sodeca.com
Export sales: ventilation@sodeca.com

PRODUCTION PLANT

Sodeca, S.L.U.

Ctra. de Berga, km 0,7
E-08580 Sant Quirze de Besora
Barcelona, SPAIN
Tel. +34 93 852 91 11
Fax +34 93 852 90 42
General sales: comercial@sodeca.com
Export sales: ventilation@sodeca.com



EUROPE

FINLAND

Sodeca Finland, Oy

HUITTINEN
Sales and Warehouse
Mr. Kai Yli-Sipilä
Metsälinnankatu 26
FI-32700 Huittinen
Tel. + 358 400 320 125
orders.finland@sodeca.com

HELSINKI
Smoke Control Solutions
Mr. Antti Kontkanen
Vilppulantie 9C
FI-00700 Helsinki
Tel. +358 400 237 434
akontkanen@sodeca.com

HYVINKÄÄ
Industrial Applications
Mr. Jaakko Tomperi
Niinistökatu 12
FI-05800 Hyvinkää
Tel. +358 451 651 333
jtomperi@sodeca.com

ITALIA

Marelli Ventilazione, S.R.L.

Sr. Christian Tosetti
Viale del Lavoro, 28
37036 San Martino B.A.
(VR), ITALY
Tel. +39 045 87 80 140
Fax +39 045 99 22 24
info@marelliventilazione.com

PORTUGAL

Sodeca Portugal, Unip. Lda.

PORTO
Rua Veloso Salgado 1120/1138
4450-801 Leça de Palmeira
Tel. +351 229 991 100
geral@sodeca.pt

LISBOA
Pq. Emp. da Granja Pav. 29
2625-607 Vialonga
Tel. +351 219 748 491
geral@sodeca.pt

ALGARVE
Rua da Alegria S/N
8200-557 Cortesões
Tel. +351 289 092 586
geral@sodeca.pt

UNITED KINGDOM

Sodeca Fans UK, Ltd.

Mr. Mark Newcombe
Tamworth Enterprise Centre
Philip Dix House, Corporation
Street, Tamworth, B79 7DN
UNITED KINGDOM
Tel. +44 (0) 1827 216 109
sales@sodeca.co.uk

AMERICA

CHILE

Sodeca Ventiladores, SpA.

Sra. Sofia Ormazábal
Santa Bernardita 12.005
(Esquina con Puerta Sur)
Bodegas 24 a 26,
San Bernardo, Santiago, CHILE
Tel. +56 22 840 5582
ventas.chile@sodeca.com

COLOMBIA

Sodeca Latam, S.A.S.

Sra. Luisa Stella Prieto
Calle7 No. 13 A-44
Manzana 4 Lote1, Montana
Mosquera, Cundinamarca
Bogotá, COLOMBIA
Tel. +57 1 756 4213
ventascolombia@sodeca.com

PERU

Sodeca Perú, S.A.C.

Sr. Jose Luis Jiménez
C/ Mariscal Jose Luis de
Orbegoso 331. Urb. El pino.
15022, San Luis. Lima, PERÚ
Tel. +51 1 326 24 24
Cel. +51 994671594
comercial@sodeca.pe

RUSSIA

Sodeca, L.L.C.

Mr. Stanislav Alifanov
Severnoye Shosse, 10 room 201
Business Park Plaza Ramstars
140105 Ramenskoye,
Moscow region, RUSSIA
Tel. +7 495 955 90 50
alifanov@sodeca.com



www.sodeca.com

