

# SWIMMING POOL DEHUMIDIFIERS

TECHNICAL DATA

		Pool surface	Extraction rate 30°C / 60%RH	Extraction rate 30°C / 80%RH	Air flow	Noise level (at 1 m dist.)	Power consumption	Heat output	Refrigerant	Dimensions netto (W x H x D)	Weight netto
<b>SERIES</b>	<b>Model</b>	m <sup>2</sup>	l/24hrs	l/24hrs	m <sup>3</sup> /h / Pa	dB (A)	W	W		mm	kg
<b>DRY 300</b>	PLASTIK Wave	30	36	48	550	42	700	1900	R410A	780 x 660 x 255	40
	SILVER									780 x 642 x 300	50
	METAL									780 x 660 x 255	40
	TTW										
	DUCT	30	32	43	500 / 200	54	800				
<b>DRY 400</b>	PLASTIK Wave	45	48	58	600	42	700	1900	R410A	780 x 660 x 255	40
	SILVER									780 x 642 x 300	50
	METAL									780 x 660 x 255	40
	TTW										
	DUCT	40	43	56	500 / 200	54	800				
<b>DRY 500</b>	PLASTIK Wave	60	66	101	800	44	1000	3500	R410A	1245 x 660 x 255	60
	SILVER									1245 x 660 x 300	77
	METAL									1245 x 660 x 255	60
	TTW									1245 x 660 x 255	75
	DUCT	50	52	68	1000 / 200	56	1150				
<b>DRY 800</b>	METAL	90	90	136	1100	46	1600	5100	R410A	1250 x 950 x 310	100
	TTW									1247 x 950 x 300	102
	DUCT	80	88	135	1100 / 170	58	1700				
<b>DRY 1200</b>	METAL	120	120	181	1200	46	2150	5250	R410A	1250 x 950 x 310	104
	TTW									1247 x 950 x 300	103
	DUCT	110	112	170	1200 / 145	60	2250				