Προδιαγραφές

Στόμιο βαρύτητας ορθογωνικό

BAP1.A / BAP1.B

Στόμιο βαρύτητας ορθογωνικό, ενδεικτικού τύπου **BAP1.A / BAP1.B** της **AIRTECHNIC**, κατασκευασμένο από ανοδιωμένο αλουμίνιο / αλουμίνιο βαμμένο σε χρώμα RAL... με 1 σειρά ομαδοποιημένα, ελεύθερα κινούμενα πτερύγια, παράλληλα στη 1η διάσταση, η κλίση των οποίων εξαρτάται απ' τη πίεση της ροής του αέρα για απομόνωση του συστήματος κλιματισμού ή εξαερισμού και προστασία από την είσοδο βροχής, φύλλων και πουλιών κατά την διακοπή της λειτουργίας του. Ο κατασκευαστής θα έχει πραγματοποιήσει μετρήσεις, των τεχνικών χαρακτηριστικών του στομίου, σε ανεξάρτητο εργαστήριο σύμφωνα με το πρότυπο ISO 5219-1984. Θα είναι κατάλληλο για εξωτερική τοποθέτηση σε τοίχο, για απόρριψη εσωτερικού αέρα (**BAP1.A**) / για λήψη νωπού αέρα (**BAP1.B**) και εμφανή τοποθέτηση με βίδες / κρυφή τοποθέτηση με ελατήρια / κρυφή τοποθέτηση με πλαίσιο στήριξης μορφής Π. Το εργοστάσιο κατασκευής θα είναι πιστοποιημένο κατά **ISO 9001:2015** (Συστήματα Διαχείρισης Ποιότητας) και κατά **ISO 14001:2015** (Συστήματα Περιβαλλοντικής Διαχείρισης).
Θα είναι κατασκευής της **AIRTECHNIC** τύπος **BAP1.A / BAP1.B**

Στόμιο βαρύτητας ορθογωνικό, χωρίς εξωτερική κορνίζα

BAP0.A / BAP0.B

Στόμιο βαρύτητας ορθογωνικό, χωρίς εξωτερική κορνίζα, ενδεικτικού τύπου **BAP0.A / BAP0.B** της **AIRTECHNIC**, κατασκευασμένο από ανοδιωμένο αλουμίνιο / αλουμίνιο βαμμένο σε χρώμα RAL... με 1 σειρά ομαδοποιημένα, ελεύθερα κινούμενα πτερύγια, παράλληλα στη 1η διάσταση, η κλίση των οποίων εξαρτάται απ' τη πίεση της ροής του αέρα για απομόνωση του συστήματος κλιματισμού ή εξαερισμού και προστασία από την είσοδο βροχής, φύλλων και πουλιών κατά την διακοπή της λειτουργίας του. Ο κατασκευαστής θα έχει πραγματοποιήσει μετρήσεις, των τεχνικών χαρακτηριστικών του στομίου, σε ανεξάρτητο εργαστήριο σύμφωνα με το πρότυπο ISO 5219-1984. Θα είναι κατάλληλο για εξωτερική τοποθέτηση σε τοίχο, για απόρριψη εσωτερικού αέρα (**BAP0.A**) / για λήψη νωπού αέρα (**BAP0.B**) και εμφανή τοποθέτηση με βίδες / κρυφή τοποθέτηση με ελατήρια / κρυφή τοποθέτηση με πλαίσιο στήριξης μορφής Π. Το εργοστάσιο κατασκευής θα είναι πιστοποιημένο κατά **ISO 9001:2015** (Συστήματα Διαχείρισης Ποιότητας) και κατά **ISO 14001:2015** (Συστήματα Περιβαλλοντικής Διαχείρισης).
Θα είναι κατασκευής της **AIRTECHNIC** τύπος **BAP0.A / BAP0.B**

Στόμιο βαρύτητας ορθογωνικό με πλαστικά πτερύγια

BAP1.A.PVC / BAP1.B.PVC

Στόμιο βαρύτητας ορθογωνικό, ενδεικτικού τύπου **BAP1.A.PVC / BAP1.B.PVC** της **AIRTECHNIC**, κατασκευασμένο από ανοδιωμένο αλουμίνιο με 1 σειρά ομαδοποιημένα, ελεύθερα κινούμενα πλαστικά πτερύγια, παράλληλα στη 1η διάσταση, η κλίση των οποίων εξαρτάται απ' τη πίεση της ροής του αέρα για απομόνωση του συστήματος κλιματισμού ή εξαερισμού και προστασία από την είσοδο βροχής, φύλλων και πουλιών κατά την διακοπή της λειτουργίας του. Ο κατασκευαστής θα έχει πραγματοποιήσει μετρήσεις, των τεχνικών χαρακτηριστικών του στομίου, σε ανεξάρτητο εργαστήριο σύμφωνα με το πρότυπο ISO 5219-1984. Θα είναι κατάλληλο για εξωτερική τοποθέτηση σε τοίχο, για απόρριψη εσωτερικού αέρα (**BAP1.A.PVC**) / για λήψη νωπού αέρα (**BAP1.B.PVC**) και εμφανή τοποθέτηση με βίδες / κρυφή τοποθέτηση με ελατήρια / κρυφή τοποθέτηση με πλαίσιο στήριξης μορφής Π. Το εργοστάσιο κατασκευής θα είναι πιστοποιημένο κατά **ISO 9001:2015** (Συστήματα Διαχείρισης Ποιότητας) και κατά **ISO 14001:2015** (Συστήματα Περιβαλλοντικής Διαχείρισης).
Θα είναι κατασκευής της **AIRTECHNIC** τύπος **BAP1.A.PVC / BAP1.B.PVC**

Προδιαγραφές

Στόμιο βαρύτητας ορθογωνικό, με πλαστικά πτερύγια, χωρίς εξωτερική κορνίζα

BAP0.A.PVC / BAP0.B.PVC

Στόμιο βαρύτητας ορθογωνικό, χωρίς εξωτερική κορνίζα, ενδεικτικού τύπου **BAP0.A.PVC / BAP0.B.PVC** της **AIRTECHNIC**, κατασκευασμένο από ανοδιωμένο αλουμίνιο / αλουμίνιο βαμμένο σε χρώμα RAL... με 1 σειρά ομαδοποιημένα, ελεύθερα κινούμενα πλαστικά πτερύγια, παράλληλα στη 1η διάσταση, η κλίση των οποίων εξαρτάται απ' τη πίεση της ροής του αέρα για απομόνωση του συστήματος κλιματισμού ή εξαερισμού και προστασία από την είσοδο βροχής, φύλλων και πουλιών κατά την διακοπή της λειτουργίας του. Ο κατασκευαστής θα έχει πραγματοποιήσει μετρήσεις, των τεχνικών χαρακτηριστικών του στομίου, σε ανεξάρτητο εργαστήριο σύμφωνα με το πρότυπο ISO 5219-1984. Θα είναι κατάλληλο για εξωτερική τοποθέτηση σε τοίχο, για απόρριψη εσωτερικού αέρα (**BAP0.A.PVC**) / για λήψη νωπού αέρα (**BAP0.B.PVC**) και εμφανή τοποθέτηση με βίδες / κρυφή τοποθέτηση με ελατήρια / κρυφή τοποθέτηση με πλαίσιο στήριξης μορφής Π. Το εργοστάσιο κατασκευής θα είναι πιστοποιημένο κατά **ISO 9001:2015** (Συστήματα Διαχείρισης Ποιότητας) και κατά **ISO 14001:2015** (Συστήματα Περιβαλλοντικής Διαχείρισης).
Θα είναι κατασκευής της **AIRTECHNIC** τύπος **BAP0.A.PVC / BAP0.B.PVC**

Διάφραγμα βαρύτητας ορθογωνικό, για αεραγωγούς

BAP2

Διάφραγμα βαρύτητας ορθογωνικό, ενδεικτικού τύπου **BAP2** της **AIRTECHNIC**, με πλαίσιο κατασκευασμένο από γαλβανισμένη λαμαρίνα, με 1 σειρά ομαδοποιημένα, ελεύθερα κινούμενα πτερύγια από αλουμίνιο, παράλληλα στη 1η διάσταση, η κλίση των οποίων εξαρτάται απ' τη πίεση της ροής του αέρα για απομόνωση του συστήματος κλιματισμού ή εξαερισμού και προστασία από την είσοδο βροχής, φύλλων και πουλιών κατά την διακοπή της λειτουργίας του. Ο κατασκευαστής θα έχει πραγματοποιήσει μετρήσεις, των τεχνικών χαρακτηριστικών του στομίου, σε ανεξάρτητο εργαστήριο σύμφωνα με το πρότυπο ISO 5219-1984. Θα είναι κατάλληλο για τοποθέτηση εντός δικτύου αεραγωγών, για απόρριψη εσωτερικού αέρα ή για λήψη νωπού αέρα. Το εργοστάσιο κατασκευής θα είναι πιστοποιημένο κατά **ISO 9001:2015** (Συστήματα Διαχείρισης Ποιότητας) και κατά **ISO 14001:2015** (Συστήματα Περιβαλλοντικής Διαχείρισης).
Θα είναι κατασκευής της **AIRTECHNIC** τύπος **BAP2**

Specifications

Rectangular gravity grille

BAP1.A / BAP1.B

Rectangular gravity grille, indicative type **BAP1.A / BAP1.B** by **AIRTECHNIC** manufactured of anodized aluminum / aluminum painted in RAL… color, with 1 row of grouped, freely moving blades, parallel to the 1st dimension, the inclination of which depends on the pressure of the air flow, in order to isolate the air conditioning or ventilation system and protect it against rain, leaves and birds when it stops operating. The manufacturer will have performed measurements of the technical characteristics of the grille, in an independent laboratory according to the standard ISO 5219-1984. It will be suitable for external wall placement, for internal air extraction (**BAP1.A**) / for fresh air supply (**BAP1.B**) and visible installation with screws / concealed installation with springs / concealed installation with Π-shaped subframe. The factory will be certified according to **ISO 9001:2015** (Quality Management Systems) and according to **ISO 14001:2015** (Environmental Management Systems).
It will be manufactured by **AIRTECHNIC** type **BAP1.A / BAP1.B**

Rectangular gravity grille, without external frame

BAP0.A / BAP0.B

Rectangular gravity grille without external frame, indicative type **BAP0.A / BAP0.B** by **AIRTECHNIC** manufactured of anodized aluminum / aluminum painted in RAL… color, with 1 row of grouped, freely moving blades, parallel to the 1st dimension, the inclination of which depends on the pressure of the air flow, in order to isolate the air conditioning or ventilation system and protect it against rain, leaves and birds when it stops operating. The manufacturer will have performed measurements of the technical characteristics of the grille, in an independent laboratory according to the standard ISO 5219-1984. It will be suitable for external wall placement, for internal air extraction (**BAP0.A**) / for fresh air supply (**BAP0.B**) and visible installation with screws / concealed installation with springs / concealed installation with Π-shaped subframe. The factory will be certified according to **ISO 9001:2015** (Quality Management Systems) and according to **ISO 14001:2015** (Environmental Management Systems).
It will be manufactured by **AIRTECHNIC** type **BAP0.A / BAP0.B**

Rectangular gravity grille with plastic blades

BAP1.A.PVC / BAP1.B.PVC

Rectangular gravity grille, indicative type **BAP1.A.PVC / BAP1.B.PVC** by **AIRTECHNIC** manufactured of anodized aluminum / aluminum painted in RAL… color, with 1 row of grouped, freely moving plastic blades, parallel to the 1st dimension, the inclination of which depends on the pressure of the air flow, in order to isolate the air conditioning or ventilation system and protect it against rain, leaves and birds when it stops operating. The manufacturer will have performed measurements of the technical characteristics of the grille, in an independent laboratory according to the standard ISO 5219-1984. It will be suitable for external wall placement, for internal air extraction (**BAP1.A.PVC**) / for fresh air supply (**BAP1.B.PVC**) and visible installation with screws / concealed installation with springs / concealed installation with Π-shaped subframe. The factory will be certified according to **ISO 9001:2015** (Quality Management Systems) and according to **ISO 14001:2015** (Environmental Management Systems).
It will be manufactured by **AIRTECHNIC** type **BAP1.A.PVC / BAP1.B.PVC**

Specifications

Rectangular gravity grille with plastic blades, without external frame

BAP0.A.PVC / BAP0.B.PVC

Rectangular gravity grille, without external frame, indicative type **BAP0.A.PVC / BAP0.B.PVC** by **AIRTECHNIC** manufactured of anodized aluminum / aluminum painted in RAL… color, with 1 row of grouped, freely moving plastic blades, parallel to the 1st dimension, the inclination of which depends on the pressure of the air flow, in order to isolate the air conditioning or ventilation system and protect it against rain, leaves and birds when it stops operating. The manufacturer will have performed measurements of the technical characteristics of the grille, in an independent laboratory according to the standard ISO 5219-1984. It will be suitable for external wall placement, for internal air extraction (**BAP0.A.PVC**) / for fresh air supply (**BAP0.B.PVC**) and visible installation with screws / concealed installation with springs / concealed installation with Π-shaped subframe. The factory will be certified according to **ISO 9001:2015** (Quality Management Systems) and according to **ISO 14001:2015** (Environmental Management Systems).
It will be manufactured by **AIRTECHNIC** type **BAP0.A.PVC / BAP0.B.PVC**

Rectangular gravity grille, for air ducts

BAP2

Rectangular gravity grille, indicative type **BAP2** by **AIRTECHNIC,** with a frame manufactured of galvanized sheet metal and 1 row of grouped, freely moving aluminium blades, parallel to the 1st dimension, the inclination of which depends on the pressure of the air flow, in order to isolate the air conditioning or ventilation system and protect it against rain, leaves and birds when it stops operating. The manufacturer will have performed measurements of the technical characteristics of the grille, in an independent laboratory according to the standard ISO 5219-1984. It will be suitable for placement within an airduct network, for internal air extraction or for fresh air supply. The factory will be certified according to **ISO 9001:2015** (Quality Management Systems) and according to **ISO 14001:2015** (Environmental Management Systems).
It will be manufactured by **AIRTECHNIC** type **BAP2**